


Xtreme Ties

11" 28 cm

**Severe Cold Temperature Applications
Indoor/Outdoor**
Aplicaciones con temperaturas frías intensas
Interiores y exteriores
Applications dans des températures très froides
Intérieur/Extérieur



Min. & Max Operating Temperature: -40°F - 185°F
Temperatura operativa: (-40°C - 85°C)
Température de fonctionnement:

Min. Bundle Diameter: 3/8" (14.3mm)
Agrupar diámetro mínimo:
Diamètre du faisceau minimum:

Max. Bundle Diameter: 3" (76.2mm)
Agrupar diámetro máximo:
Diamètre du faisceau maximum:

Min. Installation Temperature: -4°F
Temperatura mínima de instalación: (-20°C)
Température minimale d'installation:

Transport and store at room temp. 73°F
Transporte y almacene a temp. ambiente 23 °C
Transporter et entreposer à la température ambiante 23 °C (73 °F)
Non-metallic material
Material no metálico
Matériau non métallique



LISTED 28 DR
TYPE 21 PLENUM RATED
POSITIONING DEVICE



MADE IN USA

Milwaukee, WI
gardnerbender.com
ZZC926 0914
Made in USA/Hecho en
USA/Fabriqué en USA



WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm.